

WHAT IS CLAIMED IS:

1. A mobile communication terminal comprising:

a photographic apparatus rotatively connected to the terminal;

5 a magnet connected to the photographic apparatus, wherein the magnet generates a magnetic flux; and

a magnetic flux sensor connected to the terminal, wherein an image produced by the photographic apparatus is inverted when the magnetic flux sensor detects the magnetic flux.

10 2. The terminal of claim 1, wherein rotation of the photographic apparatus in a predetermined angle approximates the magnet to the magnetic flux detecting sensor.

3. The terminal of claim 2, wherein the predetermined angle ranges from approximately 150° to approximately 180°.

15 4. The terminal of claim 1, wherein the inverted image is reproduced on a display in the terminal.

5. The terminal of claim 1, wherein the terminal is a folding type mobile  
20 communication terminal, the terminal further comprising:

a lower body;

an upper body having a lower surface;

a hinge connection element rotatively connecting the lower body to the upper body;

a display which reproduces the image captured by the photographic apparatus, the display being installed on the inner surface of the upper body; and

a circuit board installed in the lower body, wherein the circuit board receives a signal emitted by the magnetic flux sensor to invert the image produced by the photographic apparatus.

5

6. The terminal of claim 5, wherein the photographic apparatus is rotatively connected to the terminal at the hinge connection element.

7. The terminal of claim 6, wherein the magnetic flux sensor is connected to the  
10 circuit board.

8. The terminal of claim 6, wherein the magnet is connected to an inner circumferential surface of the photographic apparatus.

15 9. The terminal of claim 8, wherein the magnet comprises an outer circumferential surface having a curvature approximating a curvature of the inner circumferential surface of the photographic apparatus.

10. The terminal of claim 9, wherein an adhesive fixedly secures the magnet to the  
20 photographic apparatus.

11. The terminal of claim 9, further comprising:  
a first “C” shaped guide rail formed on the inner circumferential surface of the photographic apparatus; and

a second “C” shaped guide rail formed opposite the first guide rail on the inner circumferential surface of the photographic apparatus a distance approximate to the length of the magnet, wherein the first and second guide rails receive and fixedly secure the magnet to the photographic apparatus.

5

12. A mobile communication terminal comprising:

a photographic apparatus rotatively connected to the terminal;

a magnet connected to the photographic apparatus, wherein the magnet generates a magnetic flux; and

10

a magnetic flux sensor connected to the terminal, wherein an image produced by the photographic apparatus is inverted when the magnetic flux sensor does not detect the magnetic flux.

13. The terminal of claim 12, wherein rotation of the photographic apparatus a

15

predetermined angle displaces the magnet away from the magnetic flux detecting sensor.

14. The terminal of claim 13, wherein the predetermined angle ranges from

approximately 0° to approximately 150°.

20

15. The terminal of claim 12, wherein the inverted image is reproduced on a display installed on the terminal.

16. The terminal of claim 12, wherein the terminal is a folding type mobile communication terminal, the terminal further comprising:

a lower body;

an upper body having a lower surface;

a hinge connection element rotatably connecting the lower body to the upper body;

a display which reproduces the image produced by the photographic apparatus, the

5 display being installed on the lower surface of the upper body; and

a circuit board disposed within the lower body, wherein the circuit board receives a signal emitted by the magnetic flux sensor to invert the image produced by the photographic apparatus.

17. The terminal of claim 16, wherein the photographic apparatus is rotatively  
10 connected to the terminal at the hinge connection element.

18. The terminal of claim 17, wherein the magnetic flux sensor is connected to the circuit board.

15 19. The terminal of claim 17, wherein the magnet is connected to an inner circumferential surface of the photographic apparatus.

20. The method for inverting an image produced by a photographic apparatus rotatively connected to a mobile communication terminal, the method comprising the steps of:  
20 connecting a magnet to the photographic apparatus;  
connecting a magnetic flux sensor to the terminal;  
rotating the photographic apparatus a predetermined angle such that a magnetic flux generated by the magnet is approximate to the magnetic flux sensor;  
detecting the magnetic flux;

emitting a signal corresponding to the detection of the magnetic flux; and  
inverting the image produced by the photographic apparatus.